



## SAFETY DATA SHEET

U.S. Department of Labor  
Occupational Safety & Health Administration

### Silver Film

#### SECTION 1 - IDENTIFICATION

MANUFACTURER: Andek Corporation  
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057  
TELEPHONE: 1-856-786-6900  
In an emergency, contact CHEMTREC 1-800- 424-9300;  
Outside the United States call +1-703-527-3887  
PRODUCT IDENTIFIER: Silver Film  
RECOMMENDED USE: Industrial Protection Coating

#### SECTION 2 – HAZARD IDENTIFICATION

**Skin:** Slightly irritating

**Eyes:** May cause eye irritation

**Inhalation:** High vapor concentrations are irritating to the respiratory tract.

**Ingestion:** **Do Not** ingest. Aspiration during ingestion or vomiting may cause pulmonary injury.

**SIGNAL WORD:** Warning

#### HAZARD STATEMENTS:

- Flammable liquid and vapor
- May be harmful if swallowed and enters airways
- Causes mild skin irritation
- Causes eye irritation
- May be harmful if inhaled

#### PICTOGRAMS:



#### PRECAUTIONARY STATEMENTS:

##### **Prevention:**

- **Do Not** handle until all safety precautions have been read and understood .
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Avoid breathing mist, vapors or spray.
- **Do Not** get in eyes, on skin, or on clothing
- Wash thoroughly after handling
- **Do Not** eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection .
- Use explosion-proof electrical/ventilating/light/equipment.
- Take precautionary measures against static discharge

##### **Response:**

- **Skin:** Wash with plenty of water
- **Eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.
- **Inhalation:** Remove person to fresh air and keep comfortable for breathing.
- **Ingestion:** Rinse mouth. **Do Not** induce vomiting

**Storage:**

- Store in a well ventilated place. Keep container tightly closed
- Store at temperature between 40°F and 90°F

**Disposal:**

- Waste disposal should be in accordance with existing federal, state and local environmental control laws.
- Incineration is the preferred method.

**SECTION 3 – COMPOSITION**

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>APPROX %</u>
Aluminum Metal Flake	7429-90-5	35.0
Naphtha, Light Aromatic Solvent	64742-95-6	9.0
Mineral Spirit	8052-41-3	10.0
Petroleum Hydrocarbon Resin	64742-16-1	40.0
Chlorinated Paraffin	063449-39-8	4.0
Epoxy Resin	25068-38-6	2.0

**SECTION 4 – FIRST AID MEASURES****Skin:**

- Get medical aid.
- Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing/shoes

**Eyes:**

- Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids.
- If irritation persists, seek medical attention

**Inhalation:**

- Remove person to fresh air.
- If signs/symptoms continue, get medical attention.
- Give oxygen or artificial respiration as needed.

**Ingestion:**

- **Do Not** induce vomiting.
- If vomiting does occur, have victim lean forward to prevent aspiration.
- Rinse mouth with water.
- Seek medical attention.
- Never give anything by mouth to an unconscious individual

**SECTION 5 – FIRE-FIGHTING MEASURES****Suitable (and unsuitable) extinguishing media:**

- **Small fire:** Use dry chemicals, CO<sup>2</sup>, or dry sand.
- **Large fire:** Use only dry foam
- **Do Not** use water. Product may react with water to produce flammable gases.

**Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):**

- Carbon oxides expected to be the primary hazardous combustion product.

**Special protective equipment and precautions for firefighters:**

- Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide, aluminum oxide, smoke, fumes, and unburned hydrocarbons

**Flammable Properties Classification:** OSHA/NFPA Class II Combustible Liquid.

**Flash point** 42 °C (108 °F) - closed cup

**Auto ignition temperature** 471 °C (880 °F)

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures:**

- **Do Not** inhale vapors, mist or gas.
- Ensure adequate ventilation.
- Remove all sources of ignition.
- Evacuate personnel to safe areas.
- Beware of vapors accumulating to form explosive concentrations.
- Vapors can accumulate in low areas.

### **Environmental precautions:**

- Stop leak.
- Contain spill if possible and safe to do so.
- Prevent product from entering drains.

### **Methods and materials for containment and cleaning up:**

- Absorb with an inert dry material and place in an appropriate waste disposal container.
- Keep disposal containers closed when finished.

## **SECTION 7 – HANDLING & STORAGE**

### **Precautions for safe handling:**

- **Do not** get on skin or in eyes.
- **Do not** inhale vapor or mist.
- Keep away from sources of ignition - No smoking.
- Take measures to prevent the buildup of electrostatic charge.
- Open and handle container with care.
- Metal containers involved in the transfer of this material should be grounded and bonded.

### **Recommendations on the conditions for safe storage:**

- Store in a tightly closed container and keep in a cool, dry, well-ventilated place.
- Keep container away from extreme heat and strong oxidizing agents.

## **SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION:**

### **Exposure limits:**

CHEMICAL NAME	PEL	TLV
Mineral Spirits	500 mg/m <sup>3</sup> (8h TWA)	100 mg/m <sup>3</sup> (8 h TWA)
Cumene (present <0.001%)	N/A	50ppm (8 h)
Aluminum	3 mg/m <sup>3</sup> (8 h)	5 mg/m <sup>3</sup> (respirable fraction)

### **Engineering controls:**

- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits (see below).
- An eye wash station and safety shower should be located near the work-station.

### **Individual protection measures:**

- Personal protective equipment should be selected based upon the conditions under which this material is used.
- A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations.

### **Inhalation protection:**

- The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation.
- If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used.
- Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

**Eye protection:**

- Safety glasses equipped with side shields are recommended as minimum protection in industrial settings.
- Wear goggles if splashing or spraying is anticipated.
- Have suitable eye wash water available.

**Skin and body protections:**

- None required for incidental contact.
- Use gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected.
- Use clean protective clothing if splashing or spraying conditions are present.
- Protective clothing may include long-sleeve outer garment, apron, or lab coat.
- If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower.
- Launder contaminated clothing before reuse or discard.

**Other hygienic practices and protective equipment:**

- Use good personal hygiene practices.
- Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work.
- **Do Not** use gasoline, kerosene, solvents or harsh abrasives as skin cleaners.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES:**

**Appearance:** Metallic Newtonian liquid

**Physical state:** Liquid

**Color:** Bright Silver

**Odor:** Mildly aromatic hydrocarbon odor

**Odor threshold:** 0.07ppm

**pH:** None established

**Melting point/freezing point:** -60°C

**Initial boiling point and boiling range:** 149°C to 182°C

**Flash point:** 108°F (42°C)

**Evaporation rate:** 0.2 (butyl acetate = 1)

**Flammability:** Flammable

**Upper/lower flammability or explosive limits:** (by volume) 5.7% / 0.8%

**Vapor pressure:** 0.8kPa (6mmHg)@20°C (68°F)

**Vapor density:** 4 (air = 1)

**Relative density:** 1.03kg/l

**Solubility:** Insoluble

**Partition coefficient: n-octanol/water:** None established

**Auto-ignition temperature:** 471°C (880°F)

**Decomposition temperature:** None established

**Viscosity:** 800 centipoise @20°C

**SECTION 10 – STABILITY AND REACTIVITY**

**Hazardous Polymerization:** Not expected to occur.

**Chemical stability:** Stable in normal conditions

**Incompatibility:** Strong oxidizers, acids, alkalis, halogens and halogenated compounds

**Hazardous decomposition products:** No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this SDS.

**Conditions to avoid:** Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions. With prolonged water contact together with increased heat, it is possible for a reaction that can produce flammable hydrogen gas.

## SECTION 11 – TOXICOLOGICAL INFORMATION

The following information regarding health hazards is based upon third-party research studies.

### **Effects of Acute Exposure:**

**Inhalation:** Inhalation of dust or mist can cause irritation of the eyes, nose, throat, and lungs.

**Eye Contact:** Like any foreign body, particles can cause mechanical irritation.

**Skin Contact:** This material can cause irritation if not promptly washed from the skin. This product is not expected to be absorbed through intact skin.

**Ingestion:** Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

### **Numerical measures of toxicity:**

CHEMICAL NAME	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Mineral Spirit	5,000 mg/kg	3,000 mg/kg	N/A
Aluminum	>2,000 mg/kg	N/A	>888 mg/kg
Naptha, light aromatic solvent	8,400 mg/kg	3,160 mg/kg	2,900 ppm

## SECTION 12 – ECOLOGICAL INFORMATION

Data from toxicity test (aquatic and/or terrestrial organism where available): 5 columns

CHEMICAL NAME	Algae/Aquatic Plants (EC50)	Fish (LC50)	Toxicity to Microorganism	Crustacea (Aquatic Invertebrates)
Mineral Spirit	1.2 mg/lt 72 h (Pseudokirchneriella subcapitata - green algae)	N/A	N/A	0.1 mg/lt 21 d (daphnia magna)
Naptha, light aromatic solvent	<1 mg/lt (Skeletonema costatum)	41 mg/lt 96 hr. (Pimephales promelas (fathead minnow))	N/A	EC50 - 0.95 mg/lt 48 hr. (daphnia magna)

### **Ecotoxicity:**

Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

### **Environmental Fate:**

- **Biodegradability:** Inherently biodegradable in aerobic conditions.
- **Partition Coefficient (log Kow):** >6 (based on similar materials)
- **Photodegradation:** Based on similar materials, this product will have little or no tendency to partition to air. Hydrocarbons from this product which do partition to air are expected to rapidly photodegrade.
- **Stability in Water:** Not readily susceptible to hydrolysis under aquatic conditions.
- **Distribution:** Principally to soil and sediment. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

## SECTION 13 – DISPOSAL CONSIDERATIONS

### **Waste Disposal Method:**

Waste disposal should be in accordance with existing federal, state and local environmental control laws. Incineration is the preferred method.

### **Empty Container Precautions:**

Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. **Do not** reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal.

## SECTION 14 – TRANSPORT INFORMATION

UN #	1263
UN PROPER SHIPPING NAME:	Paint
HAZARD CLASS:	3
PACKING GROUP:	III
ENVIRONMENTAL HAZARDS:	Not a marine pollutant
GUIDANCE ON TRANSPORT IN BULK:	N/A

**Transport labels required:** Flammable liquid (In the U.S., this material may be re-classified as a combustible liquid and is not regulated in containers less than 119 gallons via surface transportation.)

**SECTION 15 – REGULATORY INFORMATION**

**US Federal Regulation:**

**SARA 311/312 Hazard Categories**

CHEMICAL NAME	CWA reportable quantities	CWA Toxic Pollutants	CWA Priority Pollutants	CWA Hazardous Substances	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity RQ
Cumene (< 0.001%)	5000 lbs	Listed	N/A	Chronic Health Hazard	Acute	Required	5000 lbs

**US State Right to Know Regulations:** New Jersey, Massachusetts, Pennsylvania, Rhode Island

CHEMICAL NAME	CAS #
Cumene	98-82-8

**CA Prop 65**

CHEMICAL NAME	CAS#	
Cumene	98-82-8	< 0.001% of the total volume

**Canada:** Not Listed

**SECTION 16 – OTHER INFORMATION (HMIS RATING)**

Health	1
Flammability	2
Physical Hazard	0
Personal Protection	G

---

**Disclaimer:** Andek Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the issue date of this Safety Data Sheet (SDS). However, because the conditions of handling, use, and storage of these materials are beyond Andek Corporation's control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations contained in the SDS are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state and local laws and regulations.

---