



SAFETY DATA SHEET

U.S. Department of Labor
Occupational Safety & Health Administration

Polafloor Epoxy Primer - Part B

SECTION 1 - IDENTIFICATION

MANUFACTURER: Andek Corporation
ADDRESS: 850 Glen Avenue, Moorestown, NJ 08057
TELEPHONE: 1-856-786-6900
In an emergency, contact CHEMTREC 1-800- 424-9300;
Outside the United States call +1-703-527-3887
PRODUCT IDENTIFIER: Polafloor Epoxy Primer - Part B
RECOMMENDED USE: Industrial Floor Primer

SECTION 2 – HAZARD IDENTIFICATION

HAZARD CLASSIFICATION (EFFECTS OF EXPOSURE):

Skin: Corrosive; may cause an allergic skin reaction – Category 1. Can cause chemical burns – Category 1B.

Eyes: Causes serious eye damage – Category 1.

Ingestion: May cause burns to the mouth, throat and stomach – Oral Category 4.

SIGNAL WORD: Danger

HAZARD STATEMENTS:

- May be harmful if swallowed.
- Causes severe skin burns and eye damage.
- Causes serious eye damage.

PICTOGRAMS:



PRECAUTIONARY STATEMENTS:

Prevention:

- **Do Not** handle until all safety precautions have been read and understood.
- **Do Not** get in eyes, on skin, or on clothing.
- Wash thoroughly after handling.
- **Do Not** eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- **Skin:**
 1. Take off immediately all contaminated clothing.
 2. Rinse skin with water/ shower.
 3. If skin irritation or a rash occurs.
 4. Get medical advice/attention.
- **Eyes:**
 1. Rinse cautiously with water for several minutes.
 2. Remove contact lenses, if present and easy to do and continue rinsing.
 3. Get medical advice/attention.
- **Ingestion:**
 1. Immediately call a POISON CENTER/doctor.
 2. Rinse mouth. **Do Not** induce vomiting.

Storage:

- Store in a dry place.
- Store in a closed container.

Disposal:

- Waste disposal should be in accordance with existing federal, state and local environmental control laws.
- Incineration is the preferred method.

SECTION 3 – COMPOSITION

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>APPROX %</u>
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	40
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with Bisphenol A Diglycidyl ether homopolymer	68609-08-5	20
Benzyl alcohol	100-51-6	40

SECTION 4 – FIRST AID MEASURES

Skin:

- Rinse with plenty of water.
- Remove contaminated clothes.
- Get medical attention.

Eyes:

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Get medical attention.

Inhalation:

- Move to fresh air.
- If adverse health effects develop seek medical attention.

Ingestion:

- Do not induce vomiting.
- The victim should drink several glasses of water to dilute the ingested substance.
- If vomiting occurs naturally, keep airway clear.
- Get medical attention.
- Never give anything by mouth if the victim is rapidly losing consciousness or is unconscious or convulsing.

SECTION 5 – FIRE-FIGHTING MEASURES

Flash point: > 233.6 °F (> 112.00 °C) ASTM D3278; Setaflash Closed Cup

Flammable limits: Not determined.

Extinguishing media:

- Water Fog
- Foam.
- Carbon dioxide.
- Dry Chemical

Special fire fighting procedures:

- Wear full protective clothing.
- Wear self-contained breathing apparatus.

Unusual fire & explosion hazards: Avoid open flames and sources of ignition.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Environmental precautions: Collect rinsate for disposal.

Methods for cleaning and take-up:

- Pick up spilled material and containerize for recovery or disposal.
- Use adequate protective equipment.
- Add dry material to absorb spill (if large spill, first dike to contain).
- Flush area with dilute (5%) acetic acid.

SECTION 7 – HANDLING & STORAGE

Precautions for safe handling: Ensure that workrooms are adequately ventilated.

Recommendations on the conditions for safe storage:

- Keep container tightly sealed.
- Keep container in a well ventilated place.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Local exhaust ventilation recommended

Inhalation protection:

- Respirator with organic vapor cartridge.
- Not applicable with adequate ventilation

Eye protection:

- Wear tight fitting goggles.
- Face shield

Skin and body protections:

- Protective gloves made of plastic.
- Protective gloves made of rubber.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Low viscosity, Newtonian liquid

Physical state: Liquid

Color: Transparent, pale yellow

Odor: Ammoniacal

Odor threshold: None established

pH: 8.5

Melting point/freezing point: None established

Initial boiling point and boiling range: 437°F (225 °C)

Flash point: 230°F (110 °C)

Evaporation rate: N.V. @ ambient (0%)

Flammability (solid, gas): Combustible @ elevated temperature

Upper/lower flammability or explosive limits: None established

Vapor pressure: None established

Vapor density: None established

Relative density: 1.00 kg/l

Solubility: Slight (0.1 to 1.0%)

Partition coefficient: n-octanol/water: None established

Auto-ignition temperature: None established

Decomposition temperature: Above 383°F

Viscosity: 600 centipoises @25°C

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: None known

Hazardous polymerization: Will not occur

Hazardous decomposition products:

- None if used for intended purpose.
- No decomposition if used according to specifications.

Conditions to avoid: None if used for intended purpose.

SECTION 11 – TOXICOLOGICAL INFORMATION

General toxicological information:

Any toxicological information included in this section is based upon data associated with an analogous product.

Acute toxicity:

- **Oral:** LD50 > 200 - <= 1000 mg/kg body weight (Rat)
- **Inhalation:** Harmful by inhalation – LC50 (4 hr) :> 4.178 mg/l (Rat)
- **Dermal:** Harmful in contact with skin – LD50 :> 2,000 mg/kg (Rabbit)

Additional information:

- **Skin irritation:** Corrosive
- **Eye irritation:** Severely irritating
- **Dermal sensitization:** Sensitizing

SECTION 12 – ECOLOGICAL INFORMATION

General ecological information: The ecological evaluation of the product is based on data from the raw material and/or comparable substances.

Acute toxicity:

Fish: LC50 > 10 - <= 460 mg product/l (96 hr)

Bacterial: EC0 > 10 - <= 700 mg product/l (72 hr)

Biodegradation:

- The total of the organic components contained in the product achieve values below 60% BOD/COD or CO² liberation, or below 70% DOC reduction in tests for ease of degradability.
- Threshold values for 'readily degradable' (e.g. to OECD method 301) are not reached.

Bioaccumulation: Low bioaccumulation potential.

SECTION 13 – DISPOSAL CONSIDERATIONS**Waste Disposal Method:**

- Waste disposal should be in accordance with existing federal, state and local environmental control laws.
- Incineration is the preferred method.

Empty Container Precautions:

- Empty containers retain product residue; observe all precautions for product.
- **Do Not** heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed.
Do Not reuse without thorough commercial cleaning and reconditioning.
- If container is to be disposed, ensure all product residues are removed prior to disposal.

SECTION 14 – TRANSPORT INFORMATION

UN #	2735
UN PROPER SHIPPING NAME:	Amines, liquid, corrosive, N.O.S.
HAZARD CLASS:	8
PACKING GROUP:	III
ENVIRONMENTAL HAZARDS:	Not a marine pollutant.
GUIDANCE ON TRANSPORT IN BULK	N/A

Transport labels required: 8

SECTION 15 – REGULATORY INFORMATION

SARA 311/312 Hazard Categories: Immediate Health

TSCA 12(b) Components: None

SARA 313 Toxic Chemicals: None

SARA 302 Extremely Hazardous Substances: None

CERCLA Hazardous Chemicals: None

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

SECTION 16 – OTHER INFORMATION (HMIS RATING)

Health	3
Flammability	1
Physical Hazard	0
Personal Protection	H

Disclaimer: Andek Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the issue date of this Safety Data Sheet (SDS). However, because the conditions of handling, use, and storage of these materials are beyond Andek Corporation's control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations contained in the SDS are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state and local laws and regulations.